



HIK-KV8102-IM VILLA DOOR STATION



Features

Basic Functions

- Video intercom function
- Access control function
- Up to 16 access cards
- High-Performance Embedded SOC Processor
- One-touch calling function
- Self adaptive IR
- Weather Resistant

Video/Audio Functions

- HD video surveillance
- Noise suppression and echo cancellation
- H.264 video compression
- Low illumination

Remote Control


- Remote unlocking via client or app
- Remote call answering via client or app

Additional Features

- Tamper alarm and door status alarm
- Auto-uploads captured pictures to FTP or the client on door unlock

Specifications

Video	
Camera	CMOS Low Illumination 1.3 MP HD Colour Camera
Video Compression Standards	H.264
Resolution / Frames per second	1280 x 720 / 25 fps
Audio	
Audio Input	Build-in Omnidirectional Microphone
Audio Output	Build-in Loudspeaker
Audio Compression Standard / Rate	G.711 U / 64 Kbps
Audio Quality	Noise Suppression and Echo Cancellation
Access Control	
Internal Card Reader	Built-in IC Card Reader
Door Magnetic Detection	Detecting Door Magnetic Status
Release to Exit	REX input
Door Relay	NO/NC Relay
Illumination	
Light Supplement	White light illumination
Network	
Ethernet	1 RJ-45 10/100 Mbps Ethernet Interface
Network Protocol	TCP/IP, RTSP
Security	
Alarm and Tamper	Wall tamper
Physical	
Front Panel Material	Aluminium Alloy
Power supply / Consumption	12VDC, Power Over Network / ≤12 W
Working Temperature / Humidity	-40° C to +70° C / 10% - 90%
Dimension (L x W x H)	182 mm × 100 mm × 33 mm
Protection Level	IP65
Certification	FCC, IC, CE, C-TICK, ROHS, REACH, WEEE



Index	Description	Index	Description
1	Low Illumination Supplement Light	5	Loudspeaker
2	Built-in Camera	6	Room No. (Customized)
3	Card Induction Area	7	Microphone
4	Call Button	8	TAMPER

